

## **RACKS MURAUX à DOUBLE SECTION 19" - 550mm prof.**

### **RACK4206 – WCD6-655**

The T-racks WCD6-655 is the smallest rack in the range of double section wall mounted racks. The double section wall mounted racks are double hinged cabinets. This means that these cabinets can also be opened at the back so that you can easily reach the back of the equipment.

- 6 units in height and 550 millimeters in depth
- Double hinged cabinet
- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 21,5 kg
- 55x60x36,7 cm



### **RACK4209 – WCD9-655**

The T-racks WCD9-655 is, in terms of height, the middle version of double section wall mounted racks. The double section wall mounted racks are double hinged cabinets. This means that these cabinets can also be opened at the back so that you can easily reach the back of the equipment.

- 9 units in height and 550 millimeters in depth
- Double hinged cabinet
- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 24 kg
- 55x60x50 cm

### **RACK4212 – WCD12-655**

The T-racks WCD12-655 is the largest rack in the range of double section wall mounted racks. The double section wall mounted racks are double hinged cabinets. This means that these cabinets can also be opened at the back so that you can easily reach the back of the equipment.

- 12 units in height and 550 millimeters in depth
- Double hinged cabinet
- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 27 kg
- 55x60x63,5 cm

## **RACKS SUR PIEDS ou SUR ROULETTES 19” - 600mm prof.**

### **RACK4115 – NCB15-66**

The T-racks NCB15-66 is the smallest free standing rack for 19 inch equipment. It has a height of 15 units with a depth of 600 millimeter. It is possible to install equipment with a maximum depth of 540 millimeters. The rack is fully assembled and has a stylish black finish (RAL9004). The NCB15-66 is ideal for medium to large sized system like network, audio, video and security systems. The maximum load capacity of this cabinet is 500 kilo.


- 15 units in height and 600 millimeters in depth
- Maximum load capacity of 500 kilo
- 2 fixed shelves
- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 50 kg
- 60x60x81 cm



### **RACK4118 – NCB18-66**

The T-racks NCB18-66 is part of the serie free standing rack for 19 inch equipment. It has a height of 18 units with a depth of 600 millimeter. It is possible to install equipment with a maximum depth of 540 millimeters. The rack is fully assembled and has a stylish black finish (RAL9004). The NCB18-66 is ideal for medium to large sized system like network, audio, video and security systems. The maximum load capacity of this cabinet is 500 kilo.

- 18 units in height and 600 millimeters in depth
- Maximum load capacity of 500 kilo
- 2 fixed shelves
- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 56 kg 60x60x100 cm



## **RACK4122 – NCB22-66**

The T-racks NCB22-66 is a 22 units high free standing rack for 19 inch equipment. The free standing rack has a depth of 600 millimeter. It is possible to install equipment with a maximum depth of 540 millimeters. The rack is fully assembled and has a stylish black finish (RAL9004). The NCB22-66 is ideal for medium to large sized system like network, audio, video and security systems. The maximum load capacity of this cabinet is 500 kilo.

- 22 units in height and 600 millimeters in depth
- Maximum load capacity of 500 kilo
- 2 fixed shelves
- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 62 kg
- 60x60x120 cm

## **RACK4127 – NCB27-66**

The T-racks NCB27-66 is a free standing rack for 19 inch equipment. The free standing rack has a height of 27 units and a depth of 600 millimeter. It is possible to install equipment with a maximum depth of 540 millimeters. The rack is fully assembled and has a stylish black finish (RAL9004). The NCB27-66 is ideal for medium to large sized system like network, audio, video and security systems. The maximum load capacity of this cabinet is 500 kilo.

- 27 units in height and 600 millimeters in depth
- Maximum load capacity of 500 kilo
- 2 fixed shelves
- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 67 kg
- 60x60x140 cm

## **RACK4137 – NCB37-66**

The T-racks NCB37-66 is a 19 inch free standing rack. The free standing rack has a height of 37 units and a depth of 600 millimeter. It is possible to install equipment with a maximum depth of 540 millimeters. The rack is fully assembled and has a stylish black finish (RAL9004). The NCB37-66 is ideal for medium to large sized system like network, audio, video and security systems. The maximum load capacity of this cabinet is 500 kilo.

- 37 units in height and 600 millimeters in depth
- Maximum load capacity of 500 kilo
- 3 fixed shelves



- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 78 kg
- 60x60x180 cm

## RACK4142 – NCB42-66

The T-racks NCB42-66 is a 19 inch free standing rack. The free standing rack has a height of 42 units and a depth of 600 millimeter. It is possible to install equipment with a maximum depth of 540 millimeters. The rack is fully assembled and has a stylish black finish (RAL9004). The NCB42-66 is ideal for medium to large sized system like network, audio, video and security systems. The maximum load capacity of this cabinet is 500 kilo.

- 42 units in height and 600 millimeters in depth
- Maximum load capacity of 500 kilo
- 3 fixed shelves
- Safety glass front door
- Stylish black finish (RAL9004)
- Meets ANS/EIARS-310-D standards
- 98 kg
- 60x60x200 cm

Accessoires à retrouver sur notre tarif, notamment le best-seller :

## RACK9510

Distribution électrique pour rack ; les 8 embases PC16 sont orientées vers l'intérieur du rack, et le switch ON/OFF vers l'extérieur

