

# SPEAKER IC SERIES

## IC120

### ► Technical Data

Impedance	4Ω
Frequency Range	F (0) 120 Hz – 20 kHz
System	Line array speaker
Broadband Driver	4 x (20 x 120 mm)
Rated Driver	40 W
Maximum Power	80 W
Crossover Point	Passive: BEC Crossover Active: Bessel 6 db, 180 hz

### ► Radiation

Radiation angle, Horiz.	160°
Radiation angle, Vert.	40°
Sensitivity	88 dB / W / m
Max. Rated SPL	106 dB / W / m

### ► Housing

Material	Aluminium
Color	Black, White, Silver, Gold special on request
Number of Drivers	4
Mounting	Metal angle bracket (included)
Optional	In-Wall mounting Magnetic wall bracket Stacking adapter
Operating Temp.	0 – 100° C
Dimensions	37,5 x 1206 x 23 mm
Weight	1.2 kg
Input Connectors	Phoenix 2-pole, RM: 5,08 mm



IC120 Center Black – 714109108328	IC120 Black – 714109108537
IC120 Center White – 714109108329	IC120 White – 714109108545
IC120 Center Silver – 714109108358	IC120 Silver – 714109108602
IC120 Center Gold – 714109108342	IC120 Gold – 714109108599