SPEAKER IC-WP SERIES

IC120-WP

WATERPROOF

Technical Data

Impedance	4 Ω
Frequency Range	F (0) 120 Hz – 20 kHz
System	Line array speaker
Broadband Driver	4 x (20 x 120 mm)
Rated Driver	40 W
Maximum Power	80 W
Crossover Point	Passive: BEC Crossover Active: Bessel 6 db, 180 hz

Radiation

Radiation angle, Horiz.	160°
Radiation angle, Vert.	40°
Sensitivity	88 dB
Max. Rated SPL	106 dB

Housing

Material	Aluminium
Color	Black, White
Number of Drivers	4
Mounting	Metal angle bracket (included)
Optional	In-Wall mounting Magnetic wall bracket Stacking adapter
Operating Temp.	0 – 100° C
Dimensions	37,5 x 1206 x 23 mm
Weight	1.2 kg
Input Connectors	Sumitimo 6180-2321 + 8230-4408



IC120-WP Center Black – 4262477791119
IC120-WP Center White – 4262477791126
IC120-WP Black – 714109108191
IC120-WP White – 714109108180

BEC Akustik, Division of BEC Gesellschaft für Produktmanagement mbH
Tel.: + 49 2841 95506 - 0 | Mail: info@bec-akustik.de | www.bec-akustik.com