SPEAKER IC-WP SERIES

IC70-WP

WATERPROOF

Technical Data

Impedance	6 Ω
Frequency Range	F (0) 120 Hz – 20 kHz
System	Line array speaker
Broadband Driver	3 x (20 x 120 mm)
Rated Driver	30 W
Maximum Power	60 W
Crossover Point	Passive: BEC Crossover Active: Bessel 6 db, 180 hz

Radiation

Radiation angle, Horiz.	160°
Radiation angle, Vert.	40°
Sensitivity	86 dB
Max. Rated SPL	102 dB

Housing

Material	Aluminium
Color	Black, White
Number of Drivers	3
Mounting	Metal angle bracket (included)
Optional	In-Wall mounting Magnetic wall bracket Stacking adapter
Operating Temp.	0 – 100° C
Dimensions	37,5 x 698 x 23 mm
Weight	700 g
Input Connectors	Sumitimo 6180-2321 + 8230-4408



IC70-WP Center Black – 4262477791072
IC70-WP Center White – 4262477791089
IC70-WP Black – 714109108215
IC70-WP White – 714109108210

BEC Akustik, Division of BEC Gesellschaft für Produktmanagement mbH
Tel.: + 49 2841 95506 - 0 | Mail: info@bec-akustik.de | www.bec-akustik.com